

TECHNICAL DATA SHEET

UNIQUE POWER FLUID Q535 LDA

Product Information:

Revision index / date: A, January 2018

UNIQUE POWER FLUID Q535 LDA

Full Synthetic

Description:

Top of the range, green, fully synthetic, hydraulic fluid. It's a polyvalent fluid dedicated to different applications: Hydraulic system type. Hydractive 3, power steering's, shock absorbers, active suspensions, etc...

Product features:

- Anti-corrosion properties: complete system protection.
- prolonged systems life
- Anti-wear and anti-foam properties

Application:

Hydraulic fluid

Specifications:

ISO 7308, DIN 51524 T3, PSA S 71 2710, Fendt X 902.011.622, Man M3289, VW TL 52146, (VW G002 000 / A7/A8/G004 000), MB345.0, Volvo STD 1273.36, Ford M2C 204-A, GM1940 715/ 1940 766/B040 00 70 (OPEL).

Packaging:

12 x 1 L bottle, 1 x 20 L pail, 1 x 210 L drum

Typical data:

Characteristics	Method	Units	Typical	Mini	Maxi
Kinematic viscosity @ 100°C	ASTM D 7279	cSt	6,3	5,9	-
Kinematic viscosity @ 40°C	ASTM D 7279	cSt	18,5	18,0	19,5
Viscosity index	ASTM D 2270		334	-	-
Pour point	ASTM D 5950	°C	-55	-50	-
Density	D 20/4	-	0,831	-	-
Flash point	NF T 60103	°C	154	145	-

The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies.