TECHNICAL DATA SHEET

UNIQUE Q240

Product Information:

Revision index / date: A, January 2018

PLUS 15W40 - Q240

- Ultra Power
- Mineral

Description:

PRO 15W40 Q240 is multi grade engine oil to lubricate gasoline and Diesel engines of passenger cars.

Product features:

- Anti-wear protection
- High thermal stability
- Keep engine cleaned by limiting sludge deposits

Application:
Passenger car & light commercial vehicles engines

Specifications:
API SF/CD
MIL-L-46152B CCMC: G2 / D2

Packaging:
12 x 1 L bottle, 4 x 4 L can, 4 x 5 L can, 1 x 20 L pail, 1 x 60 L drum, 1 x 210 L drum, 1000 L

UNIQUE Petro Source
Address : Lichtenauerlaan 102-120, 3062-ME Rotterdam, Netherlands
Phone : +31 10 20 45 630
Email : info@uniquepetrosource.com
www.uniquemotoroil.com

Typical data:

Characteristics	Method	Units	Typical	Mini	Maxi
Viscosity grade	SAE-J	-	15W 40	-	-
Kinematic viscosity @ 100°C	ASTM D 445	cSt	14.2	12.5	< 16.3
Kinematic viscosity @ 40°C	ASTM D 445	cSt	104	-	-
Viscosity index			140	-	-
CCS viscosity	ASTM D 5293	mPa.s	6600	-	7000
HTHS à 150°C	CEC-L-36-A-97	mPa.s	3.8	3.5	-
Density	D 20/4	-	0.878	-	-
Poor point	ASTM D 97	°C	-32	-	-
T.B.N.	ASTM D 2896	Mg KOH/g	5.0	4.0	6.0
Sulphated ash	NF T 60 143	% masse	0.55	-	0.65
Spectrometric analysis Phosphorus Zinc Calcium Magnesium	ICP	ppm	 700 800 1000	± 20 %	
NOACK volatility	CEC-L-40-A-93	% masse	12	-	13

The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies.

UNIQUE Petro Source
Address : Lichtenauerlaan 102-120, 3062-ME Rotterdam, Netherlands
Phone : +31 10 20 45 630
Email : info@uniquepetrosource.com
www.uniquemotoroil.com