

TECHNICAL DATA SHEET

UNIQUE Q387

Product Information:

Revision index / date: A, January 2018

UNIQUE 2T SYNTHETIC Q387

Synthetic

Description:

Synthetic oil for air or liquid cooled 2-stroke engines. This oil is suitable for engines running on a fuel/oil mixture or with a separate lubrication system.

When choosing your oil, always check the instructions of the engine manufacturer.

Please note: not suitable for liquid-cooled engines requiring BIA TC-W oil.

Product features:

- Significantly reduces exhaust fumes
- Reduces pre-ignition and seepage
- Prevents the piston rings from sticking, reduces deposits in the combustion chambers and blockages in the exhaust.
- Ensures good engine lubrication

Application:

2-stroke engines on high-output motorcycles, scooters and chainsaws.

Specifications:

API TC, JASO FC/FD, ISO-L-EGD

Packaging:

12 x 1 L bottle, 1 x 20 L pail, 1 x 60 L drum, 1 x 210 L drum

Typical data:

Characteristics	Method	Units	Typical	Mini	Maxi
Viscosity grade	SAE-J	-	20/30	-	-
Kinematic viscosity @ 100°C	ASTM D 7279	cSt	9,5	6,5	-
Kinematic viscosity @ 40°C	ASTM D 7279	cSt	-	-	-
Pour point	ASTM D 5950	°C	-28	-	-
Brookfield viscosity @ -10°C		cP	2800	-	-
HTHS viscosity @ 150°C	CEC-L-36-A-97	mPa.s	-	-	-
Density	D 20/4	-	0,879	-	-
T.A.N.	-	-	Non	-	-
T.B.N.	ASTM D 2896	Mg KOH/g	2,1	1,6	3,5
Sulphated ashes	ISO/FDIS 3987	% masse	0,18	-	0,34
Elements contents	ICP	ppm			
Natrium			340	± 20 %	
Color	Visual	-	Red	-	-

The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies.