

Technical data sheet: UNIQUE Hydraulic fluids

Product Information:

Revision index / date: A, January 2018

UNIQUE Hydraulic Fluids

Mineral

Description:

Mineral-based hydraulic fluid for the hydraulic suspension and braking circuits of Citroën-branded vehicles, whose circuits are painted green.

Precautions for use:

- L.H.M. fluid is only for use in the systems of Citroën vehicles, which are painted green.
- Do not use this fluid in the systems of Citroën vehicles, which are painted black.
- Do not mix with other fluids of a different family.

Application:

Hydraulic systems

Packaging:

1 x 0.5 L

Typical data:

Characteristics	Method	Units	typical	Mini	Maxi
Kinematic viscosity @ 40°C	ASTM D 7279	cSt	20	15	25
Density @ 15°C		Kg/m ³	860	-	-
Kinematic viscosity @ -40°C	-	cSt	1750	-	-
Colour	Visual	-	Green		
Flash point		°C	121	110	-

The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies.